

Technical Specifications Double dPapillon



- Professional grade full spectrum double lamp lighting system.
- Developed for the vegetative stage of the plant or addition of blue light in the flowering stage.
- High density Vega aluminum reflector with only 1% annual depreciation.
- 6 step dimming: 50%, 70%, 85%, 100%, 110%, 120%
- Includes 2 315W CMH lamps
- Driver efficiency > 95%.
- Sealed housing with Gore-Tex ventilation plug allows for extreme air pressure fluctuation.
- Lamps & reflector easily replaceable.
- 3 Year warranty on fixture, 1 year on bulb.

Rated Mains voltage	208V-277V
Voltage range (+/- 10%)	187V-305V
Frequency	50Hz – 60Hz
Current	2,87 A typical @ 240V
Operation frequency (typical)	170 Hz
Rated Power	690W @ 240V
Inrush current	< 40A
Power factor	>0,98
Dimming type	50%, 70%, 85%, 100%, 110%, 120%
Includes 2 CMH lamps	>550 $\mu\text{mol/s}$ per lamp. Rated 16.000 hours > 90%
Weight	5,4 kg (11.9 lbs.)
Dimensions (lxwxh)	38,0 x 23,0 x 33,0 cm (18.5 x 9.1 x 13.0 inch)
www.epapillon.com	

